

 Refer to warnings and safety information on pages 3-4 and page 66.

Boston Wildcat Hot Air



Tube: EPDM

Reinforcement: Fiber, 4 Spiral or 2 Ply and Helical Wire

Cover: EPDM/Pinpricked

Color: Brown

Temperature Range: +300°F

Type Of Branding: Printed Strip

Suction: Full Vacuum

Working Pressure: 100-150 PSI (Depending on coupling)

Type Of Coupling: Cam and Groove, or Combination Nipple, Clamps—Band.

Features:

- EPDM cover
- EPDM tube
- Continuous printed brand/brown color
- Longer lengths
- Pin pricked

Advantages:

- Abrasion, heat and weather resistant
- Heat resistant (intermittent service to 350°F)
- Easy identification
- Economical; less waste
- Hot air permeation

Markets:

- Tank Trucks
- In-plant Transfer
- Construction

Applications:

- Hot air blower hose; hot, dry, non-oily air applications

| PRODUCT NUMBER | NOMINAL I.D. (IN.) | (MM) | REIN. | O.D. (IN.) | (MM) | APPROX. LBS. WEIGHT PER 100 FT. | MAX. WORKING PRESS. (PSI) | MINIMUM BEND RADIUS (IN.) | (MM) | STANDARD LENGTH |
|----------------|--------------------|-------|-------|------------|-------|---------------------------------|---------------------------|---------------------------|-------|-----------------|
| H034948-100 | 3 | 76.2 | 4 Sp | 3-47/64 | 94.9 | 230 | 150 | 9 | 228.6 | 100 |
| H034964 | 4 | 101.6 | 2 Ply | 4-39/64 | 117.1 | 290 | 100 | 11 | 279.4 | 50 |
| H034964-100 | | | | | | | | | | 100 |
| H034964-150 | | | | | | | | | | 150 |

Heat resistant (intermittent service to 350°F).