

 Refer to warnings and safety information on pages 3-4 and page 83

Boston Grey Food Transfer



Tube: Vinyl Nitrile, FDA Approved Materials
Reinforcement: Fiber, 4 Spiral and Helical Wire
Cover: Vinyl Nitrile
Color: Grey
Temperature Range: -40°F to +180°F
Type Of Branding: Impression
Suction: Full Vacuum
Working Pressure: 150 PSI (Depending on coupling)
Type Of Coupling: Cam and Groove, Combination Nipple or Swaged/Crimped/Internal Expanded, Clamps—Band.

Features:

- Vinyl nitrile cover
- Vinyl nitrile tube
- Continuous permanent brand
- Grey cover
- Smooth bore

Advantages:

- Abrasion, animal fat, oil and weather resistant
- Animal and vegetable oil resistant
- Easy identification
- Meets FDA requirements
- Rapid fluid flow
- Easy to clean

Markets:

- Food Industry
- Tank Truck
- Rail Car
- In-plant

Applications:

- Transfer by pumping, suction, and discharge of non-dairy food products
- Transfer of bulk liquid, sugar, syrups, and vegetable oils from tank trucks to candy manufacturers, bottling plants, processors, etc.

| PRODUCT NUMBER | NOMINAL I.D. (IN.) | (MM) | SPIRAL | NOMINAL O.D. (IN.) | (MM) | APPROX. LBS. WEIGHT PER 100 FT. | MAXIMUM WORKING PRESS. (PSI) | MINIMUM BEND RADIUS (IN.) | (MM) | STANDARD LENGTH (FT) |
|----------------|--------------------|-------|--------|--------------------|-------|---------------------------------|------------------------------|---------------------------|-------|----------------------|
| H038424-100 | 1-1/2 | 38.1 | 4 | 2-1/8 | 54.0 | 120 | 150 | 4 | 101.6 | 100 |
| H038432-100 | 2 | 50.8 | 4 | 2-5/8 | 66.7 | 145 | 150 | 5 | 127.0 | 100 |
| H038448-100 | 3 | 76.2 | 4 | 3-5/8 | 92.1 | 220 | 150 | 9 | 228.6 | 100 |
| H038464-100 | 4 | 101.6 | 4 | 4-5/8 | 117.5 | 315 | 150 | 11 | 279.4 | 100 |

White cover available as a made-to-order.