

CLEANING EQUIPMENT





APPLICATION: For use on either steam cleaner machines or combination steam

cleaner/pressure washer machines.

CONSTRUCTION

TUBE: Pyrosyn® synthetic rubber

COVER: Black and Red Hysunite® synthetic rubber, RMA Class B

(Medium Oil Resistance)

REINFORCEMENT: Braided (1) steel wire

TEMPERATURE: Handles steam at 325°F/163°C and 350 psi, handles hot water at

250°F/121°C and 3000 psi (2500 psi on 1/2")

PACKAGING: 500' reel, maximum 3 pieces, 50' increments coupled lengths available

BRANDING: Continuous brand "Goodyear" 3/8" Whitewater Pressure Washer 3000

psi/250°F Steam Cleaner 350 psi/325°F. Made in USA."

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and

coupling procedure.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDER CODES: 539-095 (black) 539-110 (red)

Steam Cleaner Service

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Мра.	lb./ft.	kg./m.
3/8	9.5	0.69	17.5	350	2.40	0.23	0.34
1/2	12.7	0.82	20.8	350	2.40	0.32	0.48

Note: Not recommended for cold water service. For hot water service up to 250°F, handles working pressure up to 3000 psi on 3/8", 2500 psi on 1/2".