



# CLEANING EQUIPMENT

Air &  
Multipurpose  
General Purpose  
Heavy Duty  
Push-on

Chemical  
Transfer

**Cleaning  
Equipment**

Food  
Transfer  
Washdown

Marine

Material Handling  
Abrasives  
Bulk Transfer  
Cement & Concrete

Mining

Petroleum  
Aircraft Fueling  
Dispensing  
Dock  
Transfer

Spray

Steam

Vacuum

Water  
Discharge  
Suction &  
Discharge  
Washdown

Welding

Coupling  
Systems

Appendix  
Additional  
Products  
Chemical Charts  
General  
Information  
Minimum Run  
Requirements

	Page	Superior Abrasion Cover	Oil Resistance Cover	Microban Cover	Temp Range	Non- Marking*	Wire	Textile	Coupled Assemblies
Fortress™ 1000	74	Yes	Yes	Yes	-20°F to 200°F	Yes		Yes	Yes
Fortress™ 3000	75	Yes	Yes	Yes	-20°F to 250°F	Yes	Yes		Yes
Galvanator™ 3000	55	Yes	Yes		-20°F to 250°F	Yes	Yes		Yes
Gauntlet® 1500	52	Yes	Yes		-20°F to 200°F	Yes		Yes	Yes
Gauntlet® 3000	53	Yes	Yes		-20°F to 250°F	Yes	Yes		Yes
Gauntlet® 4500	54	Yes	Yes		-20°F to 250°F	Yes	Yes		Yes
Neptune™ 1500	46				-20°F to 200°F	Yes		Yes	Yes
Neptune™ 3000	47				-20°F to 250°F	Yes	Yes		Yes
Neptune™ 4001-R	48				-20°F to 250°F	Yes	Yes		Yes
Neptune™ 4500	49				-20°F to 250°F	Yes	Yes		Yes
Neptune™ 6000	50				-20°F to 250°F	Yes	Yes		Yes
Spectra™ 1000	77				-20°F to 250°F	Yes	Yes		Yes
Spectra™ 3000	78				-20°F to 250°F	Yes	Yes		Yes
Whitewater®	51				-20°F to 250°F **	Yes	Yes		Yes

\* Nonblack Colors

\*\* Steam at 325°F and 350 psi



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear-hose.com](http://www.goodyear-hose.com).

© 2006. The Goodyear Tire & Rubber Company.

Air &  
Multipurpose  
General Purpose  
Heavy Duty  
Push-on

# CLEANING EQUIPMENT

## NEPTUNE™ 1500



**Cleaning Equipment**

Food  
Transfer  
Washdown

Marine

Material Handling  
Abrasives  
Bulk Transfer  
Cement & Concrete

Mining

Petroleum  
Aircraft Fueling  
Dispensing  
Dock  
Transfer

Spray

Steam

Vacuum

Water  
Discharge  
Suction &  
Discharge  
Washdown

Welding

Coupling  
Systems

Appendix  
Additional  
Products  
Chemical Charts  
General  
Information  
Minimum Run  
Requirements

- APPLICATION:** For pressure washer equipment, agricultural sprayers, and high-pressure air lines.
- CONSTRUCTION**
- TUBE:** Nitrile synthetic rubber
- COVER:** Blue, Gray, Red, Yellow or Black oil-resistant synthetic rubber, RMA Class B (Medium Oil Resistance)
- REINFORCEMENT:** Braided (1) synthetic yarn up through 1/2". Braided (2) synthetic yarn for 3/4".
- TEMPERATURE:** -20°F to 200°F (-29°C to 93°C)
- PACKAGING:**
- |            |   |
|------------|---|
| 1/4"-5/16" | 550' to 750' reels, max 8 pieces, 25' minimum |
| 3/8"       | 500' reels, max 3 pieces, 50' increments      |
| 1/2"-3/4"  | 450' to 550' reels, max 5 pieces, 10' minimum |
- BRANDING:** Continuous brand "Neptune 1500 3/8" 1500 psi WP. Made in USA."
- COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Coupled lengths with MxMS fittings and Kink Guards available.
- NON-STOCK/SIZES:** Refer to page 300 for special production run minimum requirements.
- ORDER CODES:**
- |                |                  |                 |
|----------------|------------------|-----------------|
| 536-374 (blue) | 536-387 (gray)   | 536-388 (black) |
| 536-574 (red)  | 536-490 (yellow) |                 |

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
1/4	6.4	0.59	15.0	1500	10.34	0.11	0.16
5/16	7.9	0.69	17.5	1500	10.34	0.15	0.22
3/8	9.5	0.75	19.1	1500	10.34	0.18	0.27
1/2	12.7	0.84	21.3	1200	8.27	0.19	0.28
3/4	19.1	1.25	31.8	1500	10.34	0.42	0.63

**Note: Not recommended for steam service.**

Neptune 1500 in 1/2" ID size is rated at a working pressure rating of 1200 psi. All other sizes listed above are rated at a working pressure of 1500 psi.



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear-hose.com](http://www.goodyear-hose.com).

© 2006. The Goodyear Tire & Rubber Company.

# CLEANING EQUIPMENT

## NEPTUNE™ 3000



- APPLICATION:** For use on pressure washer machines with working pressures up to 3000 psi.
- CONSTRUCTION**
- TUBE:** Nitrile synthetic rubber
- COVER:** Black, Blue, Yellow or Gray oil-resistant synthetic rubber, RMA Class B (Medium Oil Resistance)
- REINFORCEMENT:** Braided (1) steel wire
- TEMPERATURE:** -20°F to 250°F (-29°C to 121°C)
- PACKAGING:** 500' reel, maximum 3 pieces, 50' increments
- BRANDING:** Continuous brand "Neptune 3000 by Goodyear™ 3/8" 3000 psi WP. Made in USA."
- COUPLINGS:** Use Goodyear's pressure washing fittings with this product. See page 235 for available sizes. Refer to Goodyear's Hose Assembly Manual for crimp procedures. Coupled lengths with MxMS fittings and Kink Guards available.
- NON-STOCK/SIZES:** Refer to page 300 for special production run minimum requirements.
- ORDER CODES:** 539-085 (black) 539-089 (blue) 539-104 (yellow) 539-090 (gray)

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
1/4	6.4	0.53	13.5	3000	20.69	0.16	0.24
3/8	9.5	0.69	17.5	3000	20.69	0.24	0.36
1/2	12.7	0.82	20.8	3000	20.69	0.32	0.48

**Note: Not recommended for steam service.**

Air & Multipurpose  
General Purpose  
Heavy Duty  
Push-on

Chemical Transfer

Cleaning Equipment

Food  
Transfer  
Washdown

Marine

Material Handling  
Abrasives  
Bulk Transfer  
Cement & Concrete

Mining

Petroleum  
Aircraft Fueling  
Dispensing  
Dock  
Transfer

Spray

Steam

Vacuum

Water  
Discharge  
Suction & Discharge  
Washdown

Welding

Coupling Systems

Appendix  
Additional Products  
Chemical Charts  
General Information  
Minimum Run Requirements



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear-hose.com](http://www.goodyear-hose.com).

© 2006. The Goodyear Tire & Rubber Company.

Air &  
Multipurpose  
*General Purpose*  
*Heavy Duty*  
*Push-on*

# CLEANING EQUIPMENT

## NEPTUNE™ 4001-R



**Cleaning  
Equipment**

Food  
*Transfer*  
*Washdown*

**APPLICATION:** For high-pressure washer equipment with working pressures up to 4000 psi.

**CONSTRUCTION  
TUBE:**

Nitrile synthetic rubber

**COVER:**

Black, Yellow, Blue or Gray oil resistant synthetic rubber, RMA Class B (Medium Oil Resistance)

**REINFORCEMENT:**

Braided (1) steel wire

**TEMPERATURE:**

-20°F to 250°F (-29°C to 121°C)

**PACKAGING:**

500' reel, maximum 3 pieces, 50' increments

**BRANDING:**

Continuous brand "Goodyear™ Neptune 4001-R 3/8" 4000 psi WP. Made in USA."

**COUPLINGS:**

Use Goodyear's powerwash fittings with this product. See page 235 for available sizes. Refer to Goodyear's Hose Assembly Manual for crimp procedures. Coupled lengths with MxMS fittings and Kink Guards available.

**NON-STOCK/SIZES:**

Refer to page 300 for special production run minimum requirements.

**ORDER CODES:**

539-261 (black) 539-266 (yellow) 539-265 (blue) 539-262 (gray)

Material Handling  
*Abrasives*  
*Bulk Transfer*  
*Cement & Concrete*

Mining

Petroleum  
*Aircraft Fueling*  
*Dispensing*  
*Dock*  
*Transfer*

Spray

Steam

Vacuum

Water  
*Discharge*  
*Suction & Discharge*  
*Washdown*

Welding

Coupling  
Systems

Appendix  
*Additional Products*  
*Chemical Charts*  
*General Information*  
*Minimum Run Requirements*

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
3/8	9.5	0.69	17.5	4000	27.58	0.23	0.34

**Note: Not recommended for steam service.**



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear-hose.com](http://www.goodyear-hose.com).

© 2006. The Goodyear Tire & Rubber Company.

# CLEANING EQUIPMENT

## NEPTUNE™ 4500



- APPLICATION:** For use on pressure washer machines with working pressures up to 4500 psi.
- CONSTRUCTION**
- TUBE:** Nitrile synthetic rubber
- COVER:** Black or Blue oil-resistant synthetic rubber, RMA Class B (Medium Oil Resistance)
- REINFORCEMENT:** Braided (2) steel wires
- TEMPERATURE:** -20°F to 250°F (-29°C to 121°C)
- PACKAGING:**
- |           |  |
|-----------|--|
| 1/4"-3/8" | 500' reels, maximum 3 pieces, minimum of 50' lengths |
| 1/2"      | 500' reels, maximum 3 pieces, minimum of 50' lengths |
- BRANDING:** Continuous brand "Goodyear™ Neptune 4500 3/8" 4500 psi WP. Made in USA."
- COUPLINGS:** Use Goodyear's powerwash fittings with this product. See page 235 for available sizes. Refer to Goodyear's Hose Assembly Manual for crimp procedures. Coupled lengths with MxMS fittings and Kink Guards available.
- NON-STOCK/SIZES:** Refer to page 300 for special production run minimum requirements.
- ORDER CODES:** 539-091 (black)      539-124 (blue)

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
1/4	6.4	0.54	13.7	4500	31.03	0.21	0.31
3/8	9.5	0.69	17.5	4500	31.03	0.27	0.40
1/2	12.7	0.82	20.8	4500	31.03	0.36	0.54

**Note: Not recommended for steam service.**

Air & Multipurpose  
General Purpose  
Heavy Duty  
Push-on

Chemical Transfer

**Cleaning Equipment**

Food  
Transfer  
Washdown

Marine

Material Handling  
Abrasives  
Bulk Transfer  
Cement & Concrete

Mining

Petroleum  
Aircraft Fueling  
Dispensing  
Dock  
Transfer

Spray

Steam

Vacuum

Water  
Discharge  
Suction & Discharge  
Washdown

Welding

Coupling Systems

Appendix  
Additional Products  
Chemical Charts  
General Information  
Minimum Run Requirements



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear-hose.com](http://www.goodyear-hose.com).

© 2006. The Goodyear Tire & Rubber Company.

Air &  
Multipurpose  
*General Purpose*  
*Heavy Duty*  
*Push-on*

# CLEANING EQUIPMENT

## NEPTUNE™ 6000



Chemical  
Transfer

**Cleaning  
Equipment**

Food  
*Transfer*  
*Washdown*

Marine

Material Handling  
*Abrasives*  
*Bulk Transfer*  
*Cement & Concrete*

Mining

Petroleum  
*Aircraft Fueling*  
*Dispensing*  
*Dock*  
*Transfer*

Spray

Steam

Vacuum

Water  
*Discharge*  
*Suction &*  
*Discharge*  
*Washdown*

Welding

Coupling  
Systems

Appendix  
*Additional*  
*Products*  
*Chemical Charts*  
*General*  
*Information*  
*Minimum Run*  
*Requirements*

- APPLICATION:** For use on pressure washer machines with working pressures up to 6000 psi.
- CONSTRUCTION**
- TUBE:** Nitrile synthetic rubber
- COVER:** Black oil resistant synthetic rubber, RMA Class B (Medium Oil Resistance)
- REINFORCEMENT:** Braided (2) steel wires
- TEMPERATURE:** -20°F to 250°F (-29°C to 121°C)
- PACKAGING:** 500' reels, maximum 3 piece, 50' increments, coupled lengths available
- BRANDING:** Continuous brand "Goodyear™ Neptune 6000 3/8" 6000 psi WP. Made in USA."
- COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.
- NON-STOCK/SIZES:** Refer to page 300 for special production run minimum requirements.
- ORDER CODES:** 539-149

ID		NOM. OD		MAX. WP		WEIGHT	
<i>in.</i>	<i>mm.</i>	<i>in.</i>	<i>mm.</i>	<i>psi.</i>	<i>Mpa.</i>	<i>lb./ft.</i>	<i>kg./m.</i>
3/8	9.5	0.69	17.5	6000	41.37	0.31	0.46

**Note: Not recommended for steam service.**



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear-hose.com](http://www.goodyear-hose.com).

© 2006. The Goodyear Tire & Rubber Company.

# CLEANING EQUIPMENT

**WHITEWATER®**



- APPLICATION:** For use on either steam cleaner machines or combination steam cleaner/pressure washer machines.
- CONSTRUCTION**
- TUBE:** Pyrosyn® synthetic rubber
- COVER:** Black and Red Hysunite® synthetic rubber, RMA Class B (Medium Oil Resistance)
- REINFORCEMENT:** Braided (1) steel wire
- TEMPERATURE:** Handles steam at 325°F/163°C and 350 psi, handles hot water at 250°F/121°C and 3000 psi (2500 psi on 1/2")
- PACKAGING:** 500' reel, maximum 3 pieces, 50' increments coupled lengths available
- BRANDING:** Continuous brand "Goodyear™ 3/8" Whitewater Pressure Washer 3000 psi/250°F Steam Cleaner 350 psi/325°F. Made in USA."
- COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.
- NON-STOCK/SIZES:** Refer to page 300 for special production run minimum requirements.
- ORDER CODES:** 539-095 (black)      539-110 (red)

### Steam Cleaner Service

ID		NOM. OD		MAX. WP		WEIGHT	
<i>in.</i>	<i>mm.</i>	<i>in.</i>	<i>mm.</i>	<i>psi.</i>	<i>Mpa.</i>	<i>lb./ft.</i>	<i>kg./m.</i>
3/8	9.5	0.69	17.5	350	2.40	0.23	0.34
1/2	12.7	0.82	20.8	350	2.40	0.32	0.48

**Note: Not recommended for cold water service.** For hot water service up to 250°F, handles working pressure up to 3000 psi on 3/8", 2500 psi on 1/2".

Air & Multipurpose  
General Purpose  
Heavy Duty  
Push-on

Chemical Transfer

**Cleaning Equipment**

Food  
Transfer  
Washdown

Marine

Material Handling  
Abrasives  
Bulk Transfer  
Cement & Concrete

Mining

Petroleum  
Aircraft Fueling  
Dispensing  
Dock  
Transfer

Spray

Steam

Vacuum

Water  
Discharge  
Suction & Discharge  
Washdown

Welding

Coupling Systems

Appendix  
Additional Products  
Chemical Charts  
General Information  
Minimum Run Requirements



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear-hose.com](http://www.goodyear-hose.com).

Air &  
Multipurpose  
*General Purpose*  
*Heavy Duty*  
*Push-on*

# CLEANING EQUIPMENT

## GAUNTLET® 1500



**Cleaning Equipment**

Food  
*Transfer*  
*Washdown*

**APPLICATION:**

Goodyear Gauntlet® 1500 is for pressure washer equipment with working pressures up to 1500 psi. Its super abrasion-resistant cover provides maximum protection against adverse affects of oil and animal fats.

**CONSTRUCTION**

**TUBE:**

Nitrile synthetic rubber

**COVER:**

Black or Yellow oil-resistant Carbryn® synthetic rubber, RMA Class A (High Oil Resistance)

**REINFORCEMENT:**

Braided (1) synthetic yarn up through 1/2". Braided (2) synthetic yarn for 3/4".

**TEMPERATURE:**

-20°F to 200°F (-29°C to 93°C)

**PACKAGING:**

500' reel, maximum 3 pieces, 50' increments

**BRANDING:**

Continuous brand "Goodyear" Gauntlet 1500 3/8" 1500 psi. Made in USA."

**COUPLINGS:**

Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Coupled lengths with MxMS fittings and Kink Guards available.

**NON-STOCK/SIZES:**

Refer to page 300 for special production run minimum requirements.

**ORDER CODES:**

536-480 (black)      536-474 (yellow)

ID		NOM. OD		MAX. WP		WEIGHT	
<i>in.</i>	<i>mm.</i>	<i>in.</i>	<i>mm.</i>	<i>psi.</i>	<i>Mpa.</i>	<i>lb./ft.</i>	<i>kg./m.</i>
1/4	6.4	0.59	15.0	1500	10.34	0.11	0.16
3/8	9.5	0.75	19.1	1500	10.34	0.18	0.27
1/2	12.7	0.84	21.3	1200	8.27	0.18	0.29
3/4	19.1	1.25	31.8	1500	10.34	0.41	0.61

**Note: Not recommended for steam service.**

Gauntlet 1500 in the 1/2" ID is rated at a working pressure of 1200 psi. All other sizes listed above are rated at a working pressure of 1500 psi.

Material Handling  
*Abrasives*  
*Bulk Transfer*  
*Cement & Concrete*

Mining

Petroleum  
*Aircraft Fueling*  
*Dispensing*  
*Dock*  
*Transfer*

Spray

Steam

Vacuum

Water  
*Discharge*  
*Suction & Discharge*  
*Washdown*

Welding

Coupling Systems

Appendix  
*Additional Products*  
*Chemical Charts*  
*General Information*  
*Minimum Run Requirements*



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear-hose.com](http://www.goodyear-hose.com).

© 2006. The Goodyear Tire & Rubber Company.

# CLEANING EQUIPMENT

## GAUNTLET® 3000



- APPLICATION:** For use on pressure washer machines with working pressures up to 3000 psi. Its super abrasion-resistant cover provides maximum protection against adverse affects of oil and animal fats.
- CONSTRUCTION**
- TUBE:** Nitrile synthetic rubber
- COVER:** Black or Yellow oil-resistant Carbryn® synthetic rubber, RMA Class A (High Oil Resistance)
- REINFORCEMENT:** Braided (1) steel wire
- TEMPERATURE:** -20°F to 250°F (-29°C to 121°C)
- PACKAGING:** 500' reels, maximum 3 pieces, 50' increments
- BRANDING:** Continuous brand "Gauntlet 3000 by Goodyear™ 3/8" 3000 psi. Made in USA."
- COUPLINGS:** Use Goodyear's powerwash fittings with this product. See page 235 for available sizes. Refer to Goodyear's Hose Assembly Manual for crimp procedures. Coupled lengths with MxMS fittings and Kink Guards available.
- NON-STOCK/SIZES:** Refer to page 300 for special production run minimum requirements.
- ORDER CODES:** 539-099 (black)                      539-100 (yellow)

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
3/8	9.5	0.69	17.5	3000	20.69	0.24	0.36
1/2	12.7	0.82	20.8	3000	20.69	0.32	0.48

**Note: Not recommended for steam service.**

Air & Multipurpose  
General Purpose  
Heavy Duty  
Push-on

Chemical Transfer

**Cleaning Equipment**

Food  
Transfer  
Washdown

Marine

Material Handling  
Abrasives  
Bulk Transfer  
Cement & Concrete

Mining

Petroleum  
Aircraft Fueling  
Dispensing  
Dock  
Transfer

Spray

Steam

Vacuum

Water  
Discharge  
Suction & Discharge  
Washdown

Welding

Coupling Systems

Appendix  
Additional Products  
Chemical Charts  
General Information  
Minimum Run Requirements



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear-hose.com](http://www.goodyear-hose.com).

Air &  
Multipurpose  
*General Purpose*  
*Heavy Duty*  
*Push-on*

# CLEANING EQUIPMENT

## GAUNTLET® 4500



**Cleaning Equipment**

Food  
*Transfer*  
*Washdown*

Marine

Material Handling  
*Abrasives*  
*Bulk Transfer*  
*Cement & Concrete*

Mining

Petroleum  
*Aircraft Fueling*  
*Dispensing*  
*Dock*  
*Transfer*

Spray

Steam

Vacuum

Water  
*Discharge*  
*Suction & Discharge*  
*Washdown*

Welding

Coupling Systems

Appendix  
*Additional Products*  
*Chemical Charts*  
*General Information*  
*Minimum Run Requirements*

**APPLICATION:**

For use on pressure washer machines with working pressures up to 4500 psi. Its super abrasion-resistant cover provides maximum protection against adverse affects of oil and animal fats.

**CONSTRUCTION**

**TUBE:**

Nitrile synthetic rubber

**COVER:**

Black or Yellow oil-resistant Carbryn® synthetic rubber, RMA Class A (High Oil Resistance)

**REINFORCEMENT:**

Braided (2) steel wires

**TEMPERATURE:**

-20°F to 250°F (-29°C to 121°C)

**PACKAGING:**

1/4"–3/8" 500' reels, maximum 3 pieces, minimum of 50' lengths, coupled lengths available  
1/2" 500' reels, maximum 3 pieces, minimum of 50' lengths, coupled lengths available

**BRANDING:**

Continuous brand "Goodyear™ Gauntlet 4500 3/8" 4500 psi WP. Made in USA."

**COUPLINGS:**

Use Goodyear's powerwash fittings with this product. See page 235 for available sizes. Refer to Goodyear's Hose Assembly Manual for crimp procedures. Coupled lengths with MxMS fittings and Kink Guards available.

**NON-STOCK/SIZES:**

Refer to page 300 for special production run minimum requirements.

**ORDER CODES:**

539-122 (black) 539-120 (yellow)

ID		NOM. OD		MAX. WP		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	lb./ft.	kg./m.
1/4	6.4	0.54	13.7	4500	31.03	0.20	0.30
3/8	9.5	0.69	17.5	4500	31.03	0.28	0.42
1/2	12.7	0.82	20.8	4500	31.03	0.35	0.52

**Note: Not recommended for steam service.**



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear-hose.com](http://www.goodyear-hose.com).

© 2006. The Goodyear Tire & Rubber Company.

# CLEANING EQUIPMENT

## GALVANATOR™ 3000



- APPLICATION:** For pressure washer equipment. Its rust-resistant reinforcement and superior abrasion-resistant cover provides maximum protection against adverse affects of water, oil, and animal fats.
- CONSTRUCTION**
- TUBE:** Nitrile synthetic rubber
- COVER:** Yellow or Black Carbryn® synthetic rubber (wrapped finish), ORS, RMA Class A (High Oil Resistance)
- REINFORCEMENT:** Braided (2) steel wires
- TEMPERATURE:** -20°F to 250°F (-29°C to 121°C)
- PACKAGING:** 500' reels, maximum 3 pieces, 50' increments
- BRANDING:** Continuous brand "Galvanator 3000 by Goodyear™ 3/8" (9.5mm) 3000 psi (20.7 Mpa). Made in USA."
- COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Coupled lengths with MxMS fittings and Kink Guards available.
- NON-STOCK/SIZES:** Refer to page 300 for special production run minimum requirements.
- ORDER CODES:** 539-200 (yellow) 539-201 (black)

ID		NOM. OD		MAX. WP		BEND RADIUS		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	in.	mm.	lb./ft.	kg./m.
3/8	9.5	0.69	17.5	3000	20.69	2.5	64	0.26	0.39
1/2	12.7	0.82	20.8	3000	20.69	3.5	89	0.31	0.46

**Note: Not recommended for steam service.**

Air & Multipurpose  
General Purpose  
Heavy Duty  
Push-on

Chemical Transfer

Cleaning Equipment

Food  
Transfer  
Washdown

Marine

Material Handling  
Abrasives  
Bulk Transfer  
Cement & Concrete

Mining

Petroleum  
Aircraft Fueling  
Dispensing  
Dock  
Transfer

Spray

Steam

Vacuum

Water  
Discharge  
Suction & Discharge  
Washdown

Welding

Coupling Systems

Appendix  
Additional Products  
Chemical Charts  
General Information  
Minimum Run Requirements



See Page 2 for complete product warranty and terms of sale information. In V-Cat, please reference the Conditions of Sale page in the General Information section. Information in this catalog supersedes all previously printed material. Information valid as of the day published. Due to continual product improvements, Goodyear reserves the right to alter specs without prior notice. For the most current product information, visit us online at [www.goodyear-hose.com](http://www.goodyear-hose.com).